

TECHNICAL RIDER **STUDIO 1**

Update : 14/03/2025



Contact

Flagey vzw/asbl Rue du Belvédèrestraat 27/5 B-1050 Brussels Tel : +32(0)2 641 10 10 info@flagey.be www.flagey.be

General Information

Technical and artist entrance

Rue du Belvédèrestraat 25 B-1050 Brussels

Studio 1 is located on floor -1 Access is possible from the loading dock

Service elevator :

Width: 1,20m Depth: 2,40m Height: 2,90m

Capacity: Total: 156

Loading dock entrance: Width: 4,32m Height: 2,90m

All seats are fixed When a mixing desk is needed in the hall, this reduces the capacity by 8 seats



Stage

Stage dimensions

Width: 12 m. Clearance: 8, 18m front stage and 6,92 m backstage, (levelled stage). Depth: 11,35m


Stage risers

The stage consists of 5 **fixed** rectangular platforms, rising up towards the back of the stage and functioning as natural, built-in risers.

The studio narrows towards the back of the stage.

All additional risers have the same wooden finish as the stage and can be used for risers on stage or for a proscenium. The risers are shared between the studios and are therefore not always available:

- 6 2x1m
- 2 2x1m



Piano

One piano is permanently stocked on the stage and **cannot** be removed. Please contact your promotor / production manager if you want to make use of a grand piano. Steinway D (2015) – 442Hz Only

Acoustical treatment

Studio 1 is equipped with an original acoustic modulation system dating from the 1930. This still fulfils today's needs: the 47 rotating columns expose a reflecting or an absorbing surface, allowing a variation of reverberation time between 1.1 and 1.9 seconds.

Music stands and stage equipment

- 50 Musician chairs
- 1 High chairs
- 10 Music stands (more available in other studio's)
- 6 Guitar stands
- 5 Double bass stands

Dressing Rooms

Dressing Rooms

1 x Large dressing room (25m² - Level -1) 3-seat sofa, desk, full length mirror, fridge Private bathroom with shower and toilet Ibach warm-up grand piano

2 x dressing room (20m² - Level -1)

2seat sofa, desk, full length mirror, fridge Private bathroom with shower and toilet

Sound

Stereo FOH

FOH L/R: 2 x D&B CI9 90°x40° - on stand FOH Subs: 2x E18 , from L/R or separate send.

Mixing desks

Midas Pro2C with DL251 (at balcony or FOH) A&H SQ6 with 2x DX168 16in/8out stagebox (only at FOH) Monitors are always mixed from FOH.

Wedges

Maximum 11 wedges + PFL

- 10 D&B Max 12, 12", 60° radial
- 2 D&B Max 15, 15", 60° radial
- 8 E3 for small applications
- 10 EPAC Amps
- 2 D6 Amps

Mics

The collection has to be shared among all studios and is therefore not always entirely available. Please consult.

- 1 Shure Beta52
- 1 AKG D112
- 1 Shure Beta 91A PZM
- 5 Shure SM57
- 6 Shure SM58
- 2 Shure Beta 58A supercardioid
- 1 Shure Beta 87A supercardioid
- 1 Shure Beta 87C cardioid
- 3 Shure Beta 98A + drummounts + hornmounts
- 3 Sennheiser e604
- 3 Sennheiser MD421
- 2 Beyerdynamic M88
- 1 Electro Voice RE20
- 2 AKG C 451
- 2 AKG C414 B-ULS
- 2 AKG C41 XLS matched pair
- 2 AKG C411
- 2 Audix ADX60 PZM
- 1 Audix D1
- 2 Audix D2
- 1 Audix D4
- 4 Neumann KM184
- 2 Neumann KM185
- 2 DPA 4011
- 2 DPA 4006C
- 2 DPA 2011C
- 4 DPA 4099 + various clips
- 2 DPA SC4098-BX45 Gooseneck

- 8 Active DI BSS AR133
- 1 Apex stereo DI
- 8 Shure MX412
- 2 Shure MX418
- 2 Schertler DYN Grand piano

Flagey also has a selection of recording microphones. See below for 'recording equipment'.

Wireless Microphones

Legal frequencies in Belgium (@2015), no licence needed: TV channel 27 (518.000 MHz -526.000 MHz) max 50mWatt TV channel 29 (534.000 MHz -542.000 MHz) max 50mWatt

We are occupying a lot of frequencies in those two channels. <u>For large setups a detailed frequency planning has to be setup for feasibility.</u> <u>AND PLEASE LET US KNOW if you bring your own radio systems so we can check compatibility.</u>

KIT A: 8 channels Shure ULXD - H56 - TV channel 29

- 2 ULX-D4Q Quad receiver
- 8 ULXD2 Beta KSM9 Handheld

KIT B: 6 channels Shure ULXD - H56 - TV channel 29

- 1 ULX-D4Q Quad receiver
- 1 ULX-D2Q Dual receiver
- 6 ULXD2 Beta KSM9 Handheld

KIT C : 4 channels Shure ULXD - H56 - TV channel 29

- 1 ULX-D4Q Quad receiver H56
- 4 ULXD2 Beta KSM9 Handheld

KIT D : 2 channels Shure SLXD - H51 - TV channel 27

- 1 SLXD4DE Dual receiver
- 2 SLXD2 SM58
- 1 SLXD1 beltpack

KIT E : 2 channels Shure SLXD - H51 - TV channel 27

- 1 SLXD4DE Dual receiver H51
- 2 SLXD2 SM58
- 1 SLXD1 beltpack

VARIOUS

- 6 ULXD1 Beltpack H56
- 6 DPA 4466 OMNI headset (beige) for ULXD1
- 1 DPA D:fine dual ear DIRECTIONAL headset for ULXD1
- 1 DPA 2028 d:vote VOCAL cardio condensor head for ULXD2
- 2 B87 cardio condensor head for ULXD2

Light

The lighting setup is permanent and small adaptations are only possible for very specific situations which should ALWAYS be discussed and approved in advanced.

Mixer

Avolites Tiger Touch II + Wing Bringing your own mixing desk should ALWAYS be discussed in advance.

Sources

- 4 Robe T1 Spot
- 6 Prolights PixieWash XB300
- 12 ETC 750W Découpe Zoom/Leko fixed
- 8 ETC Par Source four 750W
- 2 PC 2kW Robert Juliat
- 4 PC 1kW Robert Juliat
- 6 Briteq Probeamer Zoom 150W
- 16 Lumipar 50W
- 11 Customized Vintage spots with Eurolite LED bars

We also have some additional spare sources, shared between the different studios. Availability should therefore always be discussed in advance.


Fog machine

DF50 hazer

Accessories

ETC Gobo holder size B10 (internal diameter : 86 mm / diameter of the image : 64,5 mm)

13 Manfrotto stand 126U (shared with other studios)



Video



Screen

Screen STUMPL white - matt - with black border - frame: 6.30 x 3.63 - Ratio image 16/9

Projector

Panasonic DLP PT-RZ670 Laser diode 6,500 lm – Resolution 1,920 x 1,200 pixels

Mixer & sources

- 1 Roland V-60HD
- 1 Roland V-1HD+
- 1 Blackmagic Atem Mini
- 1 TvOne C2-2855 universal scaler

Monitoring & clicker

Those screens are shared between all the rooms and therefore only available upon request

- 1 TV Samsung LH40DME sur totem ou support retour de scène
- 2 Samsung OM55D-W 55"
- 1 DSan perfect Cue clicker system 1 remote + 1 receptor

Flagey has an extensive collection of adapters to work with and combine different standards. SDI, NDI, Mac, PC, BNC, HDMI

Recording

Flagey is fully equipped to record and livestream all your events. All the studios are connected through a fiber optics network to a central recording facility for both audio and video.

1. Audio equipment

Pro Tools rig

Protools Ultimate 2022 + HDX thunderbolt chassis core MTRX Studio Protools I/O box Avid dock& 2x S1 controllers DAD Mon controller Mac mini Intel i9 + screens Set up at the Post-production booth but flightcase mounted. Can be used in other rooms upon request.

Preamps

DAD AX32 40 IN/8 out + 128 DANTE card with SCR, remote controlled with DADman software. Grace design m108 8 I/O, remote controlled through web browser. We use DANTE over a Fiber network between the preamps and MTRX studio (max 96k)

Fixed near field monitoring

PSI Audio A21M https://www.psiaudio.swiss/a21-m-perfectly-accurate-mid-field-monitor/ | Genelec 8341A + GLM kit & software https://www.genelec.com/8341a | Heritage RAM5000 monitor controller

Mobile near field monitoring

Genelec 8331A I Grace design M900 Headphone preamp I Focusrite AM2 Dante monitor controller en Hp preamp

Backup recorder

I JoeCoe 64ch stand alone Dante HD recorder I Macbook M1 with DVS

Recording Mics

In addition to the live/hybrid mics from page 3, flagey has the following high quality mics available for recording:

- 2 Audix ADX 60 PZM
- 2 Royer Ribbon R-10 MP
- 2 Schoeps colette MK-4

Recording

2. Video equipment

Cameras

- 4 Sony BRC-X400. SDI + NDI
- 1 RM-IP500/AC Remote
- 1 Compact 4K handy camcorder. Sony PXW-Z150
- 2 Birddog PF120 NDI + HDMI
- 2 Birddog mini 3G-SDI > NDI encoder for additional sources
- 1 Birddog studio 3G-SDI <> HDMI

Switching + recording kit

- 1 Tricaster 410+ with 3 internal recorders
- 1 Tricaster TCMinics controler
- 2 Hyperdeck Studio pro 2 recorder

Set up at the video recording booth but flightcase mounted. Can be used in other rooms upon request.

Monitoring & shading

- Black Magic Smartscope duo and various monitors available (Seetec multistandard)
- 2 Birddog studio 3G-SDI > HDMI

Streaming encoder

Data video NVS-34 – streaming encoder One source to dual output streaming Vimeo pro account and livestreaming platform available upon request

Clocking

Rosendahl Nanosync, max 48kHz Mif 4 time code generator We can provide sample accurate external clocking (Wordclock & videoburst) and Timecode and at all the recording booths.

Post-production

Adobe Premiere Pro Final Cut Pro Imac 24" 2021 – M1 Only available at the post-production booth

